

CHILLED WATER AIR HANDLER



Compact design allowing installation in smaller spaces.

Installation kit included (mounting brackets and chilled water brass fittings).

Designed and engineered for maximum efficiency.

Extra chilled water copper lines for superior heat removal.

High velocity blowers provide excellent airflow with quiet operation.

Blowers are fully insulated and rotatable for variability in installation and ducting.

Oversized corrosion-resistant stainless steel drain pan with 3/4" connections.


AIR HANDLER UNITS MEASUREMENT TABLE


Air Handlers Model:	FMZ7H	FMZ10H	FMZ12H	FMZ16H	FMZ18H	FMZ24H	FMZ36DH	FMZ36H	FMZ48DH	
A	13 ½"	13 ¾"	15"	17"	17"	17"	33 ¼"	20 ¼"	33 ¼"	
	342.9 mm	349.25 mm	381 mm	431.8 mm	431.8 mm	431.8 mm	844.55 mm	514.35 mm	844.55 mm	
В	11½"	13"	13 ¼"	14"	14"	15 ¼"	12 ¼"	17"	17"	
	285.75 mm	330.2 mm	336,55 mm	355.6 mm	355.6 mm	387.35 mm	311.15mm	431.8 mm	431.8 mm	
С	7 ½"	8 ³ ⁄ ₄ "	10 ½"	9 ¼"	9 ¼"	9 ½"	12 ½"	12 ¼"	13 ½"	
	190.5 mm	222.25 mm	266.7 mm	234.95 mm	234.95 mm	241.3 mm	317.5 mm	311.15mm	342.9 mm	
D	11¾"	12 ¾"	16 ½"	15"	15"	15 ½"	17 ¼"	19"	18 ½"	
	298.45 mm	323,85 mm	419.1 mm	381 mm	381 mm	393.7 mm	438.15 mm	482.6 mm	469.9 mm	
CHILLED WATER CONNECTIONS	1/2"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	3/4"	3/4"	


AIR HANDLER SPECIFICATION TABLE

Air Handlers Model:	FMZ7H	FMZ10H	FMZ12H	FMZ16H	FMZ18H	FMZ24H	FMZ36H/DH	FMZ48DH
Nom. Capacity BTUH	7.000	10.000	12.000	16.000	18.000	24.000	36.000	48.000
Hz	60	60	60	60	60	60	60	60
Volts	208 - 230V	208 - 230V						
FLA cool (A)	2 A	2 A	2.5 A	2.5 A	2.5 A	2.5 A	2.5 A / 4.5 A	5.0 A
FLA heat (A)	4.5 A	4.5 A	6 A	6 A	7.4 A	7.4 A	8.5 A /10.5 A	10 A
Circ. Break Min (A)	5 A	5 A	10 A	10 A	10 A	10 A	15 A	15 A
Circ. Break Max (A)	10 A	10 A	15 A	15 A	15 A	15 A	20 A	20 A













Q 2917 SW 2nd Avenue Fort Lauderdale, Florida USA - 33315