

Chilled Water Air Handler

FLOW MARINE FEATURES



TITANIUM
CONDENSERS



STAINLESS STEEL
CHASSIS



OVERSIZED
PIPING



COPPER ON COPPER
EVAPORATOR
COILS



HIGH-VELOCITY
BLOWERS



NON-PROPRIETARY
PARTS




Oversized
Stainless Steel
Drain Line



Extra Copper Lines
for High Efficiency



Copper Fins



Corrosion Resistant
Stainless Chassis
& Drain Pan



Chilled Water Air Handler: Specification Table

Chilled Water Air Handlers Model	FMZ007	FMZ010	FMZ012	FMZ016	FMZ018	FMZ024	FMZ036
Capacity BTU/h	7,000	10,000	12,000	16,000	18,000	24,000	36,000
Voltage	230v 1Ph	230v 1Ph	230v 1Ph	230v 1Ph	230v 1Ph	230v 1Ph	230v 1Ph
Max Current (A)	2A	2A	2.5A	2.5A	2.5A	3.5A	3.5A
Min. Fuse (A)	3A	3A	3.5A	3.5A	3.5A	4.5A	4.5A
Max. Fuse (A)	5A	5A	5.5A	5.5A	5.5A	6.5A	6.5A
Optional Electric Heater(A)	4.2A (1,000W)	4.2A (1,000W)	4.2A (1,000W)	4.2A (1,000W)	4.2A (1,000W)	8.4A (2,000W)	8.4A (2,000W)
Min. Fuse (A) W/ Heater	7A	7A	7A	7A	7A	12A	12A
Max. Fuse (A) W/ Heater	10A (208v~230v)	10A (208v~230v)	10A (208v~230v)	10A (208v~230v)	10A (208v~230v)	15A (208v~230v)	15A (208v~230v)
Height	11 3/8" - 289mm	13 3/8" - 340mm	13 1/2" - 343mm	14 1/4" - 362mm	14 1/4" - 362mm	15 13/4" - 400mm	17 1/4" - 438mm
Width	13 3/4" - 349mm	13 3/4" - 349mm	15 3/4" - 400mm	17 1/4" - 438mm	17 1/4" - 438mm	17 1/4" - 438mm	22 3/4" - 578mm
Pan Depth	7 1/8" - 181mm	8 1/4" - 209mm	8 1/2" - 216mm	9 1/8" - 232mm	9 1/8" - 232mm	9 1/8" - 232mm	12 1/4" - 311mm
Depth Including Blower	11 1/2" - 291mm	12 3/4" - 324mm	14 5/8" - 371mm	15 1/4" - 387mm	15 1/4" - 387mm	15 1/4" - 387mm	19" - 483mm
Chilled Water Connections	1/2"	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"
Net Weight lbs/kg	22.6lbs - 10.25kg	30.9lbs - 14.01kg	36.5lbs - 16.55kg	44.5lbs - 20.18kg	45.3lbs - 20.54kg	47.5lbs - 21.54kg	74lbs - 34kg

Dimensions
 Height (A)
 Width (B)
 Pan Depth (C)
 Depth with Blower (D)

