

World Class Marine Air Conditioning & Refrigeration

FLOW MARINE FEATURES



TITANIUM
CONDENSERS



STAINLESS STEEL
CHASSIS



OVERSIZED
PIPING



COPPER ON COPPER
EVAPORATOR
COILS



HIGH-VELOCITY
BLOWERS



NON-PROPRIETARY
PARTS

TOUCH SCREEN DISPLAY & CABLES INCLUDED



EasyTouch
Display



Extra Copper Lines
for High Efficiency



Copper Fins



Corrosion Resistant
Stainless Chassis
& Drain Pan



Self Contained Units: Specification Table

Self Contained Model	FMS007	FMS010	FMS012	FMS016	FMS024
Capacity BTU/h	7,000	10,000	12,000	16,000	24,000
Voltage	115v - 230v	115v - 230v	115v - 230v	115v - 230v	115v - 230v
Hertz/Phase	60Hz/1Ph or 50Hz/1Ph	60Hz/1Ph or 50Hz/1Ph	60Hz/1Ph or 50Hz/1Ph	60Hz/1Ph or 50Hz/1Ph	60Hz/1Ph or 50Hz/1Ph
Max Current (A)	6.1A - 3A	7.7A - 4.4A	9A - 4.7A	10.1A - 5.6A	15A
LRA (A)	29A - 15A	50A - 20A	50A - 25A	57A - 29A	63A
Power Input (W)	677w - 665w	843w - 837w	101w - 995w	110w - 1222w	2385w
Min. Fuse (A)	9A - 6A	10A - 7A	12A - 8A	13A - 8A	18A
Max. Fuse (A)	14A - 11A	15A - 12A	17A - 13A	18A - 13A	23A
Refrigerant Type	R410A	R410A	R410A	R410A	R410A
Height	11 1/4" - 286mm	12" - 305mm	14" - 356mm	13 1/8" - 333mm	15" - 381mm
Width	18" - 457mm	21" - 533mm	21" - 533mm	21" - 533mm	24" - 610mm
Depth	12" - 305mm	12" - 305mm	14 1/2" - 368mm	14 1/2" - 368mm	17" - 432mm
Seawater Connection	5/8" 16mm	5/8" 16mm	5/8" 16mm	5/8" 16mm	3/4" 20mm
Net Weight lbs/kg	54.10lbs - 24.53kg	62lbs - 28.12kg	67.14lbs - 30.45kg	78lbs - 35.38kg	118lbs - 53.52kg

Dimensions
 Height (A)
 Width (B)
 Depth (C)

